


ALL DIMENSIONS EXCLUDE INSULATION

|                         |              |
|-------------------------|--------------|
| MODEL                   | 600-SS-RH-SN |
| DESIGN CODE =           | AS1210 : 2B  |
| D/P                     | 1725 KPA     |
| T/P                     | 2165 KPA     |
| TEMP.MIN                | -40 °C       |
| TEMP.MAX                | 150 °C       |
| HAZ LEVEL               | B            |
| Seismic Design          | TS 1170.5    |
| Shell Length            | 1840 mm      |
| Aproximate Dry Weight = | 548 Kg       |
| Storage Volume =        | 381 Ltr      |
| DS = Dry Suction        | 125 NB       |
| WS = Wet Suction        | 125 NB       |
| LI = Liquid In          | 65 NB        |
| LO = Liquid Out         | 50 NB        |
| OL = Oil Drain          | 1/2" NPT     |
| C = Charging Point      | 32 NB        |
| S = Safety              | 3/4" NPT     |

Actual LCPR may vary in actual dimensions

|                              |            |   |
|------------------------------|------------|---|
| DRAWN<br>rva                 | 17/05/2026 |  <b>LOW CHARGE PRESSURE RECEIVER SYSTEMS</b><br><small>LCPRS LIMITED</small><br><small>Email: office@lcp.rs.nz</small> |
| CHECKED                      |            |   |
| APPROVED                     |            | TITLE<br><b>600-SS-RH-SN</b>  |
| SIZE                         | A3         | DWG NO<br>600-SS-RH-SN  |
| SCALE                        | 1 / 25     | REV No  |
| <b>DO NOT SCALE DRAWINGS</b> |            | SHEET 1 OF 1  |